## Sako SPECIFICATION Sako

## SAKO 85 FINNLIGHT



SAKO 85 FINNLIGHT has a series of actions which are designated: Short actions Short (S) and Short Magnum (SM), Medium action (M) and Long action (L). All metal parts are made of stainless steel or are specially coated to ensure excellent wear and corrosion resistance in different weather conditions. Magazine bottom and trigger guard are made of hard anodized aluminium for reduced weight.

The ACTIONS continue to offer traditional SAKO features such as: action sizes matched to cartridges; mechanical ejection and integral tapered scope mount rail. Additionally there is a controlled feed on all models to ensure reliable cartridge feed to the chamber on all situations (Pat. pend.).

The MAGAZINE is detachable and it can also be loaded through the ejection port. Magazine release is prevented against accidental release (Pat.pend.).

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-set trigger as option.

The SAFETY features a mechanism that allows loading and unloading of the rifle with safety engaged.

In two steps injection molded black STOCK has grey softer grip areas in the pistol grip and fore-end sides and bottoms. Black outer surfaces are Soft Touch handled.

SAKO 85 FINNLIGHT is available without open sights. Integral rails for the scope mounts are on the top of the receiver. The short, fluted, totally free-floating BARREL is cold hammer-forged of stainless steel.

## **TECHNICAL DATA**

| Action   | caliber ra        | te of twist | Overall length   |                      |
|----------|-------------------|-------------|--|----------------------|
|          | 22-250 Rem        | 14"         | S  | 1030 mm (40 1/2")    |
| S        | 243 Win           | 10"         | SM   | 1125 mm (44 5/16")   |
|          | 260 Rem           | 8"          | М  | 1085 mm (42 3/4")    |
|          | 7mm-08 Rem        | 9.5"        | L  | 1145 mm (45 1/16")   |
|          | 308 Win           | 11"         | Barrel length  |                      |
|          | 270 Win Short Mag | 10"         | S  | 515 mm (20 1/4")     |
| SM       | 300 Win Short Mag | 11"         | М  | 570 mm (22 7/16")    |
|          | 25-06 Rem         | 10"         | SM / L   | 620 mm (24 3/8")     |
| M        | 6.5x55 SE         | 8"          | Weight   | , ,                  |
|          | 270 Win           | 10"         | s  | 2.8 kg (6 3/16 lbs)  |
|          | 30-06 Sprg        | 11"         | SM / M   | 2.9 kg (6 3/8 lbs)   |
| <b>T</b> | 7mm Rem Mag       | 9.5"        | L  | 3.1 kg (6 13/16 lbs) |
| L        | 300 Win Mag       | 11"         | Length of pull   | <b>3</b> ( , ,       |
|          |                   |             | S/SM/M/L   | 355 mm (14")         |
|          |                   |             | Cartridge capacity   | ,                    |
|          |                   |             | S / M 6 rounds (1 in chamber, 5 in magazine) SM / L 5 rounds (1 in chamber, 4 in magazine) |                      |