

Trijicon ACOG® Model Specifications

Model	1.5x16S	1.5x24	2x20	3x24 XB	3x30	3.5x35	4x32	4x32 BAC	4x32 LED	5.5x50	6x48
Magnification	1.5x	1.5x	2x	3x	3x	3.5x	4x	4x	4x	5.5x	6x
Objective Lens	16mm	24mm	20mm	24mm	30mm	35mm	32mm	32mm	32mm	50mm	48mm
Eye Relief	2.4 in.	3.6 in.	2.1 in.	1.4 in.	1.9 in.	2.4 in.	1.5 in.	1.5 in.	1.5 in.	2.2 in.	2.7 in.
Exit Pupil	10.7mm	16mm	10.0mm	8.0mm	10.0mm	10.0mm	8.0mm	8.0mm	8.0mm	9.1mm	8.0mm
Field of View	7.4°	4.9°	5.6°	4.9°	3.7°	5.5°	7.0°	7.0°	7.0°	3.5°	3.3°
Field of View @ 100 yards	39 ft.	25.6 ft.	29.5 ft.	25.6 ft.	19.3 ft.	28.9 ft.	36.8 ft.	36.8 ft.	36.8 ft.	18.4 ft.	17.0 ft.
Adjustment Increments	2 clicks per in. @ 100 yds.	3 clicks per in. @ 100 yds.	2 clicks per in. @ 100 yds.	9 clicks per in. @ 30 yds.	4 clicks per in. @ 100 yds.	3 clicks per in. @ 100 yds.	2 clicks per in. @ 100 yds.	2 clicks per in. @ 100 yds.	2 clicks per in. @ 100 yds.	5 clicks per in. @ 100 yds.	4 clicks per in. @ 100 yds.
Length	4.0 in.	5.8 in.	5.3 in.	5.0 in.	6.1 in.	8.0 in.	5.8 in.	5.8 in.	6 in.	12.0 in.	9.0 in.
Weight	4.5 with Special Ring Mount 4.9 oz. with M16 Base	5.6 oz.	5.5 oz.	5.89 oz.	11.64 oz. with mount	14.0 oz.	10.4 oz.	10.6 oz.	16.1 oz. with mount and battery	25.6 oz. with mount	39.3 oz. with mount
Illumination Source	Fiber Optics and Tritium	Fiber Optics and Tritium	Fiber Optics and Tritium	Fiber Optics and Tritium	Fiber Optics and Tritium	Fiber Optics and Tritium	Tritium	Fiber Optics and Tritium	LED Powered by a AA Battery	Fiber Optics and Tritium	Fiber Optics and Tritium
											