

Trijicon AccuPoint® Model Specifications

Model	1-4x24	3-9x40	2.5-10x56	5-20x50
Magnification	1x-4x	3x-9x	2.5x-10x	5x-20x
Eye Relief	3.2 in. (Constant)	3.6 to 3.2 in.	4.1 to 2.8 in.	3.8 to 4.1 in.
Exit Pupil	17.5mm to 5.1mm	13.3mm to 4.4mm	16.3mm to 5.6mm	10mm to 2.5mm
Field of View @ 100 yds	97.5 ft. to 24.2 ft.	33.8 ft. to 11.3 ft.	37.6 ft. to 10.1 ft.	19.1 ft. to 5.1 ft.
Adjustment Increments	4 clicks per in. @ 100 yds.	4 clicks per in. @ 100 yds.	4 clicks per in. @ 100 yds.	1/4 MOA per click (.25 MOA per click)
Reticle Dimensions Triangle	16.7 MOA to 4.2 MOA	6.0 MOA to 2.0 MOA	6.3 MOA to 1.7 MOA	3.2 MOA to 0.8 MOA
Reticle Dimensions Dot	3.6 MOA to 0.9 MOA	1.3 MOA to 0.4 MOA	1.4 MOA to 0.4 MOA	0.7 MOA to 0.2 MOA
Reticle Options	Triangle Post and German #4 Crosshair	Triangle Post, MIL-Dot Crosshair and Standard Duplex Crosshair	Triangle Post, MIL-Dot Crosshair and Standard Duplex Crosshair	Triangle Post, MIL-Dot Crosshair and Standard Duplex Crosshair
Length	10.3 in.	12.4 in.	13.8 in.	13.6 in. without sunshade 16.6 in. with sunshade
Tube Diameter	30mm	1 in.	30mm	30mm
Weight	14.4 oz.	13.4 oz.	20.7 oz.	26.9 oz. without sunshade 29.4 oz. with sunshade
				