

Trijicon RMR® Model Specifications

Model	Trijicon RMR® LED	Trijicon RMR® Adjustable LED	Trijicon RMR® Dual-Illuminated
Magnification	1x	1x	1x
Sight Window	22mm x 16mm	22mm x 16mm	22mm x 16mm
Elevation Adjustment Range	436cm @ 100m (157 in. @ 100 yds.)	436cm @ 100m (157 in. @ 100 yds.)	436cm @ 100m (157 in. @ 100 yds.)
Windage Adjustment Range	436cm @ 100m (157 in. @ 100 yds.)	436cm @ 100m (157 in. @ 100 yds.)	436cm @ 100m (157 in. @ 100 yds.)
Recoil Resistance	1,100g	1,100g	1,100g
Operation Temperature Range	-40°C to +49°C / -40°F to +120°F	-40°C to +49°C / -40°F to +120°F	-40°C to +49°C / -40°F to +120°F
Storage Temperature Range	-40°C to +71°C / -40°F to +160°F (without battery)	-40°C to +71°C / -40°F to +160°F (without battery)	-40°C to +71°C / -40°F to +160°F
Power Supply	3V with 1 x CR2032 (Lithium)	3V with 1 x CR2032 (Lithium)	Tritium & Fiber Optics
Dimensions (L x W x H)	1.8 in. x 1.1 in. x 1 in. (45mm x 28mm x 25mm)	1.8 in. x 1.2 in. x 1 in. (45mm x 30mm x 25mm)	1.8 in. x 1.2 in. x 1 in. (45mm x 30mm x 26mm)
Weight	1.2 oz. (34 grams) with battery	1.17 oz. (33.2 grams) with battery	1.2 oz. (34 grams)
Lens	Tempered Glass	Tempered Glass	Tempered Glass
Body	Forged Aluminum	Forged Aluminum	Forged Aluminum
Battery Life	Up to 2 years of typical use*, up to 5 years in dark storage	Over 4 years of continuous use*, at setting 4 of 8	N/A
			

*When used at 70°F (21°C). Extreme temperatures (high or low) will affect lithium battery performance.